



Lexmark CX950se

Versatile. Simple. Sustainable.













Lexmark CX950se

With the new CX950se colour A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints - up to 25 pages per minute*. Intuitively navigate the 25 cm colour touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

Versatile: Easy to Use

Create everything your business requires and anything you can imagine - from standard office documents to marketing brochures, booklets and posters - with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

Print vivid, colourful visualisations, charts and documents with professional colour features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

Easily incorporate your multifunction printer into your workspace with a versatile, configurable design that saves space without sacrificing performance.

Boost your productivity with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+languages.

Further your organisation's digital transformation with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



Simple: Easy to Manage

Quickly do what you need to do using an intuitive operator panel and easy-to-follow navigation.

Easily maintain your devices with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

Enjoy the peace of mind of knowing you are protected by the industry's most comprehensive security portfolio, right out of the box.

Keep your business running with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

Rest easy that every aspect of your device is made to work together seamlessly thanks to Lexmark's core technology ownership.

Sustainable: Easy to feel good about

Feel good about your purchase and help meet your own sustainability goals with our world-class practices and independent third-party certifications.

Do your part for the planet with our industry-leading use of post-consumer recycled materials.

Save energy - and money - with technology that exceeds strict global standards for energy efficiency.


Minimise your impact on the environment with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

Lexmark CX950se



	809 x 592 x 660 mm
2	500-Sheet output bin Dimensions included as part of base model
3	150-Sheet multipurpose feeder Dimensions included as part of base model
4	550-Sheet tray Dimensions included as part of base model
5	550-Sheet Tray 163 x 587 x 649 mm
6	2 x 550-Sheet Tray 314 x 587 x 649 mm
7	2000 Shoot Tandom Tray A4

- 7 **2000-Sheet Tandem Tray A4** 314 x 587 x 649 mm
- 8 **Cabinet** 247 x 587 x 660 mm
- 9 **1500-Sheet High-Capacity Tray** 290 x 342 x 545 mm

10	Paper Transport Unit 143 x 412 x 466 mm	79L0H20	Toner Cartridge Lexmark CX950, 951, 833, XC9525, 9535, 8355 Cyan 46.9K
11	Folding Paper Transport Unit 184 x 612 x 555 mm	79L0H30	Toner Cartridge Lexmark CX950, 951, 833,
12	500-Sheet Staple Finisher 150 x 546 x 523 mm	79L0H40	XC9525, 9535, 8355 Magenta 46.9K Toner Cartridge Lexmark CX950, 951, 833,
13	Offset Stacker 107 x 420 x 489 mm	79L3HC0	XC9525, 9535, 8355 Yellow 46.9K Toner Cartridge Lexmark CX950, 951, 833 Cyan
14	1250-Sheet Staple 2/4 Hole Punch Finisher	79L3HK0	Return Programme 46.9K Toner Cartridge Lexmark CX950, 951, 833 Black
15	995 x 575 x 610 mm 2250-Sheet Booklet Staple 2/4 Hole		Return Programme 47.7K Toner Cartridge
	Punch Finisher 995 x 650 x 613 mm	79L3HM0	Lexmark CX950, 951, 833 Magenta Return Programme 46.9K Toner Cartridge
	Standard	79L3HY0	Lexmark CX950, 951, 833 Yellow Return Programme 46.9K Toner
	Optional		Cartridge

P/N

20L8800

20L8801

20L8802

20L8803

20L8804

20L8810

20L8811

20L8812

20L8813

20L8814

20L8815

20L8816

20L8817

Paper Handling

2 x 550-Sheet Tray

2,000-Sheet Tandem Tray - A4

1,500-Sheet High-Capacity Tray

2,000-Sheet Tandem Tray -

500-Sheet Staple Finisher

Folding Paper Transport Unit

1250-Sheet Staple 2/3 Hole

1250-Sheet Staple 2/4 Hole

2250-Sheet Booklet Staple 2/3

2250-Sheet Booklet Staple 2/4

550-Sheet Tray

Punch Finisher

Punch Finisher

Offset Stacker

Hole Punch Finisher

Hole Punch Finisher

Paper Transport Unit

Letter

P/N Memory Options

57X0070 Removable Hard Disk Enclosure

Kit

P/N Application Solutions

57X0225 Desktop Contactless Reader 57X0235 Contactless Front Solutions

Module (Primary Choice)

57X0300 Contact Authentication Device 57X0301 Contactless Authentication

Device

82S12O3 IPDS License 82S12O4 Bar Code License

P/N Connectivity

1021231 Parallel (10') Cable 1021294 USB (2 Meter) Cable

14F0100 RS-232C Serial Interface Card 27X0142 Lexmark MarkNet™ N8230 Fiber Ethernet Print Server

37X6146 Fax Card Option 57X7040 English Keyboard Kit

Surge Protective Device, 220-240V

220-240V

P/N Furniture

SPD0002

20L8806 Cabinet 20L8807 Keyboard Shelf

Product Specifications	Lexmark CX950se		
Printing			
Display	Lexmark e-Task 10-inch (25 cm) class colour touch screen		
Print Speed	Up to: Black: 25 ppm ¹ (A4) / Colour: 25 ppm ¹ (A4)		
Time to First Page	as fast as: Black: TBD seconds / Colour: TBD seconds		
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality / Colour: 4800 Colour Quality, 1200 x 1200 dpi		
Memory	Standard: 4 GB / Maximum: 4 GB		
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available		
Recommended Monthly Page Volume	4,000 - 20,000 pages ²		
Maximum Monthly Duty Cycle	Up to: 100 000 pages per month ³		
Copying			
Copy Speed	Up to: Black: 25 cpm ¹ (A4) / Colour: 25 cpm ¹ (A4)		
Time to First Copy	as fast as: Black: TBD seconds / Colour: TBD seconds		
Scanning			
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)		
A4/Ltr Duplex Scan Speed / Duplex Scan Speed (A4/Ltr	Up to: Black: 200/200 sides per minute / Colour): 200/200 sides per minute		
A4/Ltr Simplex Scan Speed / Scan Speed (A4/Ltr	Up to: Black: 100/100 sides per minute / Colour): 100/100 sides per minute		
ADF Paper Input Capacity	Up to: 200 pages 75 gsm bond		
Supplies 4			
Laser Cartridge Yields	up to: 46,900 ⁵ -page Colour (CMY) Cartridges / up to: 47,700 ⁵ -page Black Cartridge		
Imaging Unit Estimated Yield	Up to: 225,000 (black) and 250,000 (colour) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage		
Cartridge(s) Shipping with Product	5,000 ⁵ -page Black and Color (CMYK) Toner Cartridges ⁵		
Paper Handling			
Included Paper Handling	500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder		
Optional Paper Handling	2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray		
Paper Input Capacity	Up to: Standard: 700 pages 75 gsm bond / Maximum: 4750 pages 75 gsm bond		
Paper Output Capacity	Up to: Standard: 500 pages 75 gsm bond / Maximum: 2650 pages 75 gsm bond		
Media Types Supported	Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide		
Media Sizes Supported	A6, Oficio, 304.8 x 483 mm, 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope		
General Information			
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)		
Optional Network Ports / Optional Local Ports	MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial		
Noise Level	Operating: TBD dBA (Print) / TBD dBA (Copy) / TBD dBA (Scan)		
Specified Operating Environment	Altitude: 0 - 2896 metres / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)		
Product Warranty	1-Year Onsite Repair, Next Business Day		
Size / Weight	H x W x D: 809 x 592 x 660 mm / TBD kg		
ENERGY STAR Typical Electricity Consumption	TEC: TBD kilowatt-hours per week		

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

 $\hbox{@\,}2024$ Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.