



Lexmark CS943de

Large-format colour printing flexibility



Lexmark CS943de

The Lexmark CS943de colour printer is designed for security, usability and reliability for large workgroups at speeds up to 55 pages per minute*. The simplified, intuitive 10.9 cm touchscreen makes handling your print jobs easy.

Flexible input and output

- ▶ Print large-format paper sizes slightly larger than SRA3+ (up to 329 x 483 mm).
- ▶ Standard input capacity is 1,140 pages; optional additional trays expand paper input capacity up to 5,140 pages.
- ▶ Several finishing options are available: staple finisher, staple hole punch finisher, booklet finisher or Lexmark's first trifold/Z-fold finisher.

Secure by design

- ▶ Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between.
- ▶ Always improving security, we now include a standard Trusted Platform Module**, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

Enhance professional image with brilliant colour for large-format printing

- ▶ Enjoy vibrant colour with standard advanced features like PANTONE® calibration and Lexmark Named Colour

Replacement for consistent branding and professional appearance.

- ▶ Replacement cartridges yield up to 52,000/26,000 black/colour pages***.

Always focused on sustainability

- ▶ CS943de is designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.

Power up with IoT

- ▶ Our sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** The Trusted Platform Module (TPM) is not available in some countries.

*** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Lexmark CS943de



- 1 **Printer with 10.9 cm touch screen**
714 x 620 x 743 mm
- 2 **100-Sheet multipurpose feeder**
Dimensions included as part of base model
- 3 **2 x 520-Sheet tray**
Dimensions included as part of base model
- 4 **400-Sheet output bin**
Dimensions included as part of base model
- 5 **2 x 520-Sheet Tray**
305.2 x 668.5 x 720 mm
- 6 **2,000-Sheet Tandem Tray with Casters**
305.2 x 668.5 720 mm
- 7 **Caster Spacer**
305 x 669 x 720 mm
- 8 **Envelope Tray**
89.9 x 619.9 x 565.5 mm

- 9 **2,000-Sheet Tray (sidecar)**
491 x 751 x 526 mm
- 10 **Dual Catch Bin**
125 x 474 x 380 mm
- 11 **Inline Staple Finisher**
238 x 478 x 460.5 mm
- 12 **Tri-Fold/Z-Fold Booklet Finisher**
991 x 232 x 726 mm
- 13 **Booklet Staple (2/3) Hole Punch Finisher**
1056 x 790 x 589 mm
- 14 **Staple (2/3) Hole Punch Finisher**
983 x 962 x 653 mm



| | |
|------------|---|
| P/N | Hardware |
| 32D0016 | Lexmark CS943de |
| P/N | Supplies |
| 73D0HCO | Lexmark CS943 Cyan 26K Toner Cartridge |
| 73D0HKO | Lexmark CS943 Black 52K Toner Cartridge |
| 73D0HMO | Lexmark CS943 Magenta 26K Toner Cartridge |
| 73D0HYO | Lexmark CS943 Yellow 26K Toner Cartridge |
| 73D0P00 | Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 Black 165K Photoconductor |
| 73D0Q00 | Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 3-Pack 165K Photoconductor Kit |
| 73D0W00 | Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 35K Waste Container |

| | |
|------------|--|
| P/N | Paper Handling |
| 32D0810 | Caster Spacer |
| 32D0811 | 2 x 520-Sheet Tray with Casters |
| 32D0812 | 2,000-Sheet Tandem Tray with Casters |
| 32D0813 | Envelope Tray |
| 32D0816 | 2,000-Sheet Tray (sidecar) |
| 32D0819 | Dual Catch Bin |
| 32D0820 | Inline Staple Finisher |
| 32D0823 | Staple (2/3) Hole Punch Finisher |
| 32D0824 | Staple (2/4) Hole Punch Finisher |
| 32D0825 | Booklet Staple (2/3) Hole Punch Finisher |
| 32D0826 | Booklet Staple (2/4) Hole Punch Finisher |
| 32D0842 | Tri-Fold/Z-Fold Booklet Finisher |

| | |
|------------|----------------------------------|
| P/N | Memory Options |
| 27X0400 | 500+ GB Hard Disk |
| 57X9528 | Intelligent Storage Device (ISD) |

| | |
|------------|-----------------------------------|
| P/N | Application Solutions |
| 57X0300 | Contact Authentication Device |
| 57X0301 | Contactless Authentication Device |
| 82S1203 | IPDS License |
| 82S1204 | Bar Code License |

| | |
|------------|---|
| P/N | Connectivity |
| 1021294 | USB (2 Meter) Cable |
| 14F0100 | RS-232C Serial Interface Card |
| 27X0142 | Lexmark MarkNet™ N8230 Fiber Ethernet Print Server |
| 27X6410 | Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server |
| 57X7040 | English Keyboard Kit |
| SPD0002 | Surge Protective Device, 220-240V |

You can install one of the following: the Dual Catch Bin or the Inline Staple Finisher or the Staple Hole Punch Finisher or the Booklet Staple Hole Punch Finisher. To install the Tri-Fold/Z-Fold Finisher, you must also install the Booklet Staple Hole Punch Finisher. To install the Staple Hole Punch Finisher or Booklet Staple Hole Punch Finisher, you must also install the 2x520-Sheet Tray with Casters, the 2,000-Sheet Tandem Tray with Casters, or the Caster Spacer. To install the 2,000-Sheet Tray (sidecar), you must also install the 2x520-Sheet Tray with Casters or the 2,000-Sheet Tandem Tray with Casters. It will not work with the Caster Spacer. To install the Envelope Tray, you must remove Tray 1 and replace it with the Envelope Tray.

Product Specifications

Lexmark CS943de

| Printing | |
|---|--|
| Display | Lexmark e-Task 10.9 cm colour touch screen with audible feedback |
| Print Speed | Up to: Black: 55 ppm ¹ (A4) / Colour: 55 ppm ¹ (A4) |
| Time to First Page | as fast as: Black: 4.9 seconds / Colour: 4.9 seconds |
| Print Resolution | Black: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi) |
| Memory | Standard: 4096 MB / Maximum: 4096 MB |
| Hard Disk | Intelligent Storage Drive available; Magnetic Hard Disk available |
| Recommended Monthly Page Volume | 7,000 - 50,000 pages ² |
| Maximum Monthly Duty Cycle | Up to: 270 000 pages per month ³ |
| Supplies ⁴ | |
| Laser Cartridge Yields | up to: 26,000 ⁵ -page Colour (CMY) Cartridges / up to: 52,000 ⁵ -page Black Cartridge |
| Cartridge(s) Shipping with Product | 18,500 ⁵ -page Black Toner Cartridge ⁵ , 11,500 ⁵ -page Color (CMY) Toner Cartridges ⁵ |
| Paper Handling | |
| Included Paper Handling | 100-Sheet Multipurpose Feeder, 2 x 520-Sheet Tray, 400-Sheet Output Bin |
| Optional Paper Handling | Booklet staple hole punch finisher, Inline Stapler, Dual Catch Bin, Envelope Tray, 2 x 520-Sheet Tray/Caster, Caster spacer, Tri-fold/Z-fold booklet finisher, Staple Punch Finisher, 2000-Sheet Tray, 2000-Sheet Tandem Tray/Caster |
| Paper Input Capacity | Up to: Standard: 1140 pages 75 gsm bond / Maximum: 5140 pages 75 gsm bond |
| Paper Output Capacity | Up to: Standard: 400 pages 75 gsm bond / Maximum: 2000 pages 75 gsm bond |
| Media Types Supported | Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide |
| Media Sizes Supported | A6, Oficio, 7 3/4 Envelope, JIS-B4, 9 Envelope, B5, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope |
| General Information | |
| Standard Ports | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B) |
| Optional Network Ports / Optional Local Ports | MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option / Internal RS-232C serial |
| Noise Level | Operating: 50 dBA (Print) |
| Specified Operating Environment | Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 2500 metres / Temperature: 10 to 32°C (50 to 90°F) |
| Product Warranty | 1-Year Onsite Repair, Next Business Day |
| Size / Weight | H x W x D: 714 x 620 x 743 mm / 82.5 kg |
| ENERGY STAR Typical Electricity Consumption | TEC: 0.86 kilowatt-hours per week |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



lexmark.com.ph