



 Lexmark™

---

# Lexmark MS632dwe

??

---



# Lexmark MS632dwe

MS632dwe 47 **31,000**

## Trusted Platform Module (TPM)

Lexmark TPM Trusted Platform Module (TPM) Common Criteria and Federal Information Processing Standard (FIPS)

## Energy Star, Blue Angel, RoHS, EPEAT Silver

Energy Star®, Blue Angel, RoHS, EPEAT® Silver

## ISO/IEC 24734 (ESAT)

ISO/IEC 24734 (ESAT)



## IoT

IoT

## Lexmark Unison™ Toner

Lexmark Unison™ Toner

\* ISO/IEC 24734 (ESAT) [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds)  
\*\* Average Continuous Mono [www.lexmark.com/yields](http://www.lexmark.com/yields) ISO/IEC 19752 [www.lexmark.com/yields](http://www.lexmark.com/yields) Lexmark Unison™ Toner  
\*\*\* Lexmark Cartridge Collection Programme (LCCP)  
\*\*\* Trusted Platform Module (TPM)



Lexmark e-Task

Table with 2 columns: Feature Name and Value. Rows include: Lexmark e-Task (10.9%), 47 pages (A4), 6 pages, 1200 x 1200 dpi, 1024 MB / 1024 MB, 2,000 - 20,000 pages, 175,000 pages per month, 31,000 pages, 75,000 pages per print job, 5,000-page Return Program Toner Cartridge, 100 pages, 250 pages, 550 pages, 650 pages 75 gsm bond, 250 pages 75 gsm bond, A6, Oficio, 7 3/4, 9, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5, Statement, C5, Executive, DL, Folio, 10, USB 2.0 Specification (Type A/B), MarkNet N8230 Fiber Ethernet Print Server, 56 dBA, 10-15% duty cycle, 307.7 x 399 x 389.4 mm, Typical Electricity Consumption: 0.61 kilowatt-hours per week.

Lexmark e-Task (10/100/1000) USB 2.0 Specification (Type A) Specification (Type B), 802.11b/g/n/ac + BLE, MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial, 56 dBA, 10-15% duty cycle, 307.7 x 399 x 389.4 mm, ENERGY STAR: TEC: 0.61 kilowatt-hours per week.

