



Lexmark MC3426adw

Productivity. Reliability. Security.





We back this product with a guarantee that covers repair actions including the cost of spare parts in the first three years. The guarantee also offers you free 24-hour self-help online support and access to technical support by phone during working hours. Offer applies if the product is registered within 90 days from the date of purchase. Supplies and/or consumable parts, such as fuser or transfer unit, are excluded. Please refer to the detailed terms and conditions available at lexmark.com/myguarantee.

Lexmark MC3426adw

Small workgroup colour versatility is easy to deploy and share with the compact, lightweight Lexmark MC3426adw multifunction. It combines printing at up to 24 ppm* with automatic scanning at up 90 images per minute plus copying and faxing. Take control with a 7.2 cm touch screen and connect via Wi-Fi and more.

Compact colour versatility

- Get rich, vibrant colour output or copies at up to 24 pages per minute*, plus automatic two-sided scanning at up 90 images per minute.
- Tackle your workload with the power of a 1-GHz dual-core processor and 1 GB of memory.
- Compact dimensions of 344.4 mm high x 411.2 mm wide x 394.1 mm deep help it fit almost anywhere.
- Analogue fax provides additional document sending and receiving options.



Connect and command

- Connect via Wi-Fi, Gigabit Ethernet, or USB.
- Simplify mobile printing with the Lexmark Mobile Print app, Google Cloud Print, Mopria®, and AirPrint.
- Take command of device settings and monitor vital system functions on a 7.2 cm colour touch screen.
- Built-in cloud connectors let you securely save scans to

and retrieve files from popular cloud services Box, DropBox, Google Drive, and Microsoft OneDrive.

Sustained output, enduring quality

- Genuine Unison™ replacement toner offers rich, vibrant colour in available Extra High Yield cartridges that provide up to 4,500 pages of output** for more printing and less downtime.
- Single-piece cartridge simplifies supply replacement for fewer interruptions.
- Optional input trays increase total input capacity to 751 sheets to support longer print runs and enhanced media flexibility.
- A steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

 Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.

Save paper, save energy

- Automatic two-sided printing is standard.
- Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Lexmark MC3426adw



- 1 Multifunction product with 2 7.2 cm touch screen 344.4 x 411.2 x 394.1 mm
- 250-Sheet tray Dimensions included as part of base model
- **250-Sheet Tray** 103.9 x 411.2 x 381.0 mm

3

4

250-Sheet Tray 103.9 x 411.2 x 381.0 mm



Supports up to two optional 250-sheet trays. All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Product Specifications	Lexmark MC3426adw
Printing	
Display	2.8 inch (7.2 cm) LCD touch panel
Print speed	up to: black: 24 ppm ¹ (A4) / colour: 24 ppm ¹ (A4)
Time to first page	as fast as: black: 10.8 seconds / colour: 11 seconds
Print resolution	black: 4800 CQ (2400 x 600 dpi) / colour: 4800 CQ (2400 x 600 dpi)
Memory	Standard: 1 GB / Maximum: 1 GB / standard: 1024 MB / maximum: 1024 MB
Hard Disk	Not available
Recommended monthly page volume	750 - 5000 pages ²
Maximum monthly duty cycle	up to: 75000 pages per month ³
Copying	
Copy speed	up to: black: 24.7 cpm ¹ (A4) / colour: 24.7 cpm ¹ (A4)
Time to first copy	as fast as: black: 13.1 seconds / colour: 13.1 seconds
Scanning	
Scanner type / ADF scan	Flatbed scanner with ADF / DADF (single pass Duplex)
Duplex scan speed	up to: black: 90 / 96 spm (A4) / colour: 40 / 42 spm (A4)
Simplex scan speed	up to: black: 45 / 48 spm (A4) / colour: 20 / 21 spm (A4)
ADF paper input capacity	up to: 50 pages
Faxing	
Modem speed	Max is 33,600 bps, V.34 Half-Duplex kbps
Supplies ⁴	
Cartridge yields	up to: 4,500 ⁵ -page Black and Colour (CMYK) Extra High Yield Cartridges / up to: 1500 ⁵ -page black and colour (CMY) cartridges
Cartridge(s) shipped with product	1500 ⁵ -page black Return Program toner cartridge, 1500 ⁵ -page colour (CMY) Return Program toner cartridges
Paper Handling	
Standard paper handling	100-Sheet Output Bin, Integrated Duplex, Single-sheet manual feed, 250-sheet input
Paper input capacity	up to: standard: 250+1 pages / maximum: 750+1 pages
Paper output capacity	up to: standard: 100 pages / maximum: 100 pages
Media types supported	Hagaki card, Paper Labels, Card Stock, Plain Paper, Glossy paper, Refer to the Paper & Specialty Media Guide
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁶	
Standard connectivity	Front Hi-Speed USB port (compatible with USB 2.0 specification, type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000; RJ-45)
Noise Level	Operating: 51/52 dBA (Print) / 50 dBA (Copy) / 44 dBA (Scan)
Specified operating environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 meters / Temperature: 10 to 32°C (50 to 90°F)
Product guarantee	4 Year Guarantee (register) On Site Service
Size / Weight	HxWxD: 344.4 x 411.2 x 394.1 mm / 19.4 kg
Energy Star Typical Electricity Consumption	TEC: 0.37 kWh per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2020 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademark of Google, LLC. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/).

