



Lexmark CX735adse

Security and performance















Lexmark CX735adse

The Lexmark CX735adse is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 50 ppm*. Single-pass two-sided scanning, ultrasonic multifeed detection, and a 25 cm tablet-like touchscreen make handling your print jobs easy. Toner cartridges that yield up to 28,000/16,200 black/colour pages** keep you going.

Made to last. Easy to upgrade.

- With durable steel frames, long-life components and highyield cartridges, printers are intentionally engineered to last seven years or more.
- Long-lasting Unison™ Toner delivers consistently outstanding print quality, reduces internal wear on longlife components, and protects the print system.
- Easily upgradeable to the latest apps and security features.



Faster performance and ease of use

- Scanning is fast and accurate thanks to the single-pass two-sided automatic document feeder with ultrasonic multifeed detection.
- The large, tablet-like, button-free touchscreen will help you intuitively complete every task, from the basic to the complex.
- An Intelligent Storage Drive (ISD) is standard on this model, providing faster startup, faster data retrieval and more reliability.

Make a statement with professional colour

Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money. Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

Secure by design

- Lexmark security features help keep your information safe

 in the document, on the device, over the network and at
 all points in between.
- Always improving security, we now include a standard Trusted Platform Module***, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

Sustainability matters

- Designed for the circular economy.
- Automatic two-sided printing is standard, along with builtin energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

Power up with IoT

- Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

^{***} The Trusted Platform Module (TPM) is not available in some countries.

Lexmark CX735adse



- 1 Multifunction product with 25 cm touch screen 621 x 479 x 533 mm
- 2 550-Sheet tray with 100-sheet multipurpose feeder Dimensions included as part of base model
- 3 **550-Sheet Tray** 119 x 463 x 483 mm
- 4 550-Sheet Tray 119 x 463 x 483 mm
- 5 **550-Sheet Tray** 119 x 463 x 483 mm

- 6 **550-Sheet Tray** 119 x 463 x 483 mm
- 7 Adjustable Stand 521 x 653 x 625 mm
- 8 Convenience Stapler HV 82 x 109 x 121 mm



Standard



Optional

Lexmark CS/CX730, 735, C/ XC4342, C/XC4352 Black 150K 71C0Z10 Imaging Unit 71C0Z50 Lexmark CS/CX730, 735, C/ XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit 71C20C0 Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge Lexmark CS/CX730, 735 Black 71C20K0 Return Programme 5K Toner Cartridge Lexmark CS/CX730, 735 71C20M0 Magenta Return Programme 5K Toner Cartridge Lexmark CS/CX730, 735 Yellow 71C20Y0 Return Programme 5K Toner Cartridge 81C0X10 Lexmark CX735 Black 28K Toner Cartridge 81C0X20 Lexmark CX735 Cyan 16.2K Toner Cartridge Lexmark CX735 Magenta 16.2K 81C0X30 Toner Cartridge Lexmark CX735 Yellow 16.2K 81C0X40 Toner Cartridge 81C2XC0 Lexmark CX735 Cyan Return Programme 16.2K Toner Cartridge 81C2XK0 Lexmark CX735 Black Return Programme 28K Toner Cartridge Lexmark CX735 Magenta Return 81C2XM0 Programme 16.2K Toner Cartridge Lexmark CX735 Yellow Return 81C2XY0 Programme 16.2K Toner Cartridge P/N **Paper Handling** 40C2100 550-Sheet Tray 47C4593 Convenience Stapler P/N **Memory Options** 27X0400 500+ GB Hard Disk 57X0070 Removable Hard Disk Enclosure P/N **Application Solutions** 57X0300 Contact Authentication Device 57X0301 Contactless Authentication Device 82S12O3 **IPDS** Licence 8251204 **Bar Code Licence** P/N Connectivity USB Cable - 2 Metre 1021294 MarkNet N8370 Wireless for CS720, CS725, CX725 27X0823 27X6410 Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server SPD0002 Surge Protective Device, 220-240V P/N **Furniture** 40C2300 Adjustable Stand

P/N

P/N

47C9693

71C0W00

Hardware

Supplies

Container

Lexmark CX735adse

Lexmark CS/CX730, 735, C/

XC4342, C4352 170K Waste

Product Specifications	Lexmark CX735adse
Printing	
Display	Lexmark e-Task 25 cm (10-inch) class colour touch screen
Print Speed	Up to: Black: 50 ppm ¹ (A4) / Colour: 50 ppm ¹ (A4)
Time to First Page	as fast as: Black: 5.6 seconds / Colour: 6.1 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 4800 Colour Quality (2400 x 600 dpi), 1200 x 1200 dpi
Memory	standard: 2048 MB / maximum: 2048 MB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available
Recommended Monthly Page Volume	2,000 - 20,000 Pages ²
Maximum Monthly Duty Cycle	Up to: 150,000 pages per month ³
Copying	
Copy Speed	Up to: Black: 50 cpm ¹ (A4) / Colour: 50 cpm ¹ (A4)
Time to First Copy	as fast as: black: 5.7 seconds / colour: 6.3 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Mono: 98 / 104 sides per minute / Colour: 98 / 104 sides per minute
A4/Ltr Simplex Scan Speed	Up to: Mono: 49 / 52 sides per minute / Colour: 49 / 52 sides per minute
ADF Paper Input Capacity	Up to: 100 pages 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies ⁴	
Laser Cartridge Yields	up to: 28,000 ⁵ -page Black Extra High Yield Cartridge / up to: 16,200 ⁵ -page Colour (CMY) Extra High Yield Cartridges
Imaging Unit Estimated Yield	Up to: 150,000 pages, based on 3 average letter/A4-size pages per print job and \sim 5% coverage 6
Cartridge(s) Shipping with Product	5,000 ⁵ -page Black and Colour (CMYK) Return Programme Toner Cartridges ⁵
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 650 pages 75 gsm bond / Maximum: 2,850 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 300 pages 75 gsm bond / Maximum: 300 pages 75 gsm bond
Media Types Supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Speciality Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁷	
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional Network Ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 53 dBA (Print) / 56 dBA (Copy) / 51 dBA (Scan)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2,896 Metres (9,500 Feet)
Product Guarantee	1-Year Onsite Service, Next Business Day
Size / Weight	H x W x D: 621 x 479 x 533 mm / 39.5 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.69 kilowatt-hours per week

 $All \ information \ is \ subject \ to \ change \ without \ notice. \ Lexmark \ is \ not \ liable \ for \ any \ errors \ or \ omissions.$

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance TM word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain licence/agreement conditions. See www.lexmark.com/printerlicense for details.