



Lexmark CS331dw

Malen. Pouzdan. Sigurno.

Unaprijedite produktivnost male radne skupine uz ispis do 24 stranice u boji po minuti*, zamjenske spremnike s tonerom velikog kapaciteta te bežičnu povezivost, USB i Ethernet od jednog gigabita - sve je ovo uključeno uz Lexmark CS331dw. Njegov višezegreni procesor od 1 GHz omogućuje vam rješavanje velikih zadataka, a Lexmarkov pun spektar sigurnosti pomaže u zaštiti vaših podataka.

Kompaktna moć boje

- ▶ Ostvarite ispis u boji do 24 stranice po minuti*.
- ▶ Izadite na kraj s radnim opterećenjem ispisa uz procesor snage 1 GHz i 512 MB memorije.
- ▶ Povežite standardnom bežičnom mrežom, Ethernetom od jednog gigabita i USB-om.
- ▶ Pojednostavnite mobilni ispis uz Lexmarkovu aplikaciju za mobilni ispis, kao i tehnologije Mopria® i AirPrint .
- ▶ Dvolinijski zaslon omogućuje vam konfiguraciju, interakciju i praćenje vitalnih informacija sustava.

Jednostavno za postavljanje, jednostavno za održavanje

- ▶ Kompaktne dimenzije od 243,7 mm visine x 411,2 mm širine x 394,1 mm dubine omogućavaju postavljanje gotovo bilo gdje.



- ▶ Unison™ Toner zamjenski spremnici pružaju do 4500 stranica** ispisa visoke kvalitete.
- ▶ Čelični okvir i dugotrajne slikovne komponente znače dugovječnost uz minimalno održavanje.

Robusna, ugrađena sigurnost

- ▶ Lexmarkova arhitektura s punim spektrom sigurnosti pomaže vam u očuvanju sigurnosti informacija - u dokumentu, na uređaju, na mreži i na svim međutočkama.

Stvoreno za planet Zemlju

- ▶ Ugrađeni način uštede energije koji se iz stanja mirovanja budi i vraća u mirovanje bez ikakvog postavljanja.
- ▶ Pisač posjeduje rejting EPEAT® Silver*** te certifikat ENERGY STAR®.
- ▶ Reciklirajte spremnike putem nagrađivanog Programa prikupljanja spremnika tvrtke Lexmark (LCCP).



* Brzine ispisa i kopiranja mjerene u skladu s ISO/IEC 24734, odnosno ISO/IEC 24735 (ESAT). Za više informacija posjetite: www.lexmark.com/ISOspeeds.

** Prosječni deklarirani kapacitet spremnika za neprekinuti crno-bijeli ili neprekinuti kompozitni ispis u boji (CMY) u jednostranom (simplex) načinu rada do navedenog broja standardnih stranica u skladu s ISO/IEC 19798. Stvarni kapacitet znatno odstupa u ovisnosti o brojnim čimbenicima. Posjetite www.lexmark.com/yields za više informacija.

*** EPEAT rejting može odstupati ovisno o lokaciji. Posjetite www.epeat.net za status registracije po zemljama.

Product Specifications
Lexmark CS331dw
Printing

Display	2-line All Points Addressable (APA) monochrome LCD display
Print Speed	Up to: Black: 24 ppm ¹ (A4) / Colour: 24 ppm ¹ (A4)
Time to First Page	As fast as: Black: 10.9 seconds / Colour: 10.9 seconds
Print Resolution	Black: 4800 CQ (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi)
Memory	Standard: 512 MB / Maximum: 512 MB
Hard Disk	Not Available
Recommended Monthly Page Volume	600 - 2500 pages ²
Maximum Monthly Duty Cycle	Up to: 50000 pages per month ³

Supplies⁴

Laser Cartridge Yields	up to: 4,500 ⁵ -page Black High Yield Cartridge / up to: 4,500 ⁵ -page Colour (CMY) High Yield Cartridges / up to: 1,500 ⁵ -page Black and Colour (CMYK) Cartridges
Cartridge(s) Shipping with Product	750 ⁵ -page Black Return Programme Toner Cartridge ⁵ , 500 ⁵ -page Colour (CMY) Return Programme Toner Cartridge ⁵

Paper Handling

Included Paper Handling	100-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed, 250-Sheet Input
Paper Input Capacity	Up to: Standard: 250+1 pages 75 gsm bond / Maximum: 250+1 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 100 pages 75 gsm bond / Maximum: 100 pages 75 gsm bond
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope

General Information⁶

Standard Connectivity	802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Ethernet 10/100/1000 BaseTX (RJ-45)
Noise Level	Operating: 52 dBA (Print)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3048 Metres (10,000 Feet) / Temperature: 10 to 32°C (50 to 90°F)
Product Guarantee	1-Onsite Repair, 3 -5 Business Days
Size / Weight	H x W x D: 243.7 x 411.2 x 394.1 mm / 16.1 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.31 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2019. Lexmark. Sva prava pridržana.

Lexmark, logotip Lexmark i Unison robni su znaci tvrtke Lexmark International, Inc., registrirani u Sjedinjenim Državama i/ili drugim zemljama. AirPrint i logotip AirPrint su robni znaci tvrtke Apple, Inc. Google Cloud Print™ je robni znak tvrtke Google, LLC. Mopria® i logotipi Mopria® Logo™ i Mopria® Alliance su registrirani robni znaci i znaci usluga tvrtke Mopria Alliance, Inc. u Sjedinjenim Državama i drugim zemljama. Neovlaštena uporaba je najstrože zabranjena. Svi su drugi robni znaci imovina njihovih vlasnika. Ovaj proizvod uključuje softver koji je OpenSSL projekt razvio za uporabu u Open SSL kompletu alata (<http://www.openssl.org/>).



lexmark.rs