



# Lexmark CX962tse

Versatile. Simple. Sustainable.















#### Lexmark CX962tse

With the new CX962tse color A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints — up to 45 pages per minute\*. Intuitively navigate the 10-inch (25 cm) color touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

### Versatile: Easy to Use

Create everything your business requires and anything you can imagine — from standard office documents to marketing brochures, booklets and posters — with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

**Print vivid, colorful visualizations, charts and documents** with professional color features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

**Easily incorporate your multifunction printer into your workspace** with a versatile, configurable design that saves space without sacrificing performance.

**Boost your productivity** with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+languages.

**Further your organization's digital transformation** with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



### Simple: Easy to Manage

**Quickly do what you need to do** using an intuitive operator panel and easy-to-follow navigation.

**Easily maintain your devices** with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

**Enjoy the peace of mind of knowing you are protected** by the industry's most comprehensive security portfolio, right out of the box.

**Keep your business running** with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

Rest easy that every aspect of your device is made to work together seamlessly thanks to Lexmark's core technology ownership.

## Sustainable: Easy to feel good about

Feel good about your purchase and help meet your own sustainability goals with our world-class practices and independent third-party certifications.

**Do your part for the planet** with our industry-leading use of post-consumer recycled materials and our award-winning cartridge recycling program.

**Save energy — and money** — with technology that exceeds strict global standards for energy efficiency.

**Minimize your impact on the environment** with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

<sup>\*</sup> Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

<sup>\*\*</sup> Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

#### Lexmark CX962tse


9.7 x 23.1 x 26.0 in.

290 x 342 x 545 mm

11.4 x 13.5 x 21.4 in.

9

1500-Sheet High-Capacity Tray



Standard

Optional

20L8800

20L8801

20L8802

20L8803

20L8804

20L8810

20L8811 20L8812

20L8813

550-Sheet Tray

Punch Finisher

Punch Finisher

Letter

2 x 550-Sheet Tray

2,000-Sheet Tandem Tray - A4

1,500-Sheet High-Capacity Tray

2,000-Sheet Tandem Tray -

500-Sheet Staple Finisher Folding Paper Transport Unit

1250-Sheet Staple 2/3 Hole

1250-Sheet Staple 2/4 Hole

20L8814 2250-Sheet Booklet Staple 2/3

Hole Punch Finisher

20L8815 2250-Sheet Booklet Staple 2/4

Hole Punch Finisher

20L8816 Offset Stacker 20L8817 Paper Transport Unit

P/N Memory Options

27X0420 500GB Hard Disk Drive (SATA)

P/N Application Solutions
57X0225 Desktop Contactless Reader
57X0235 Contactless Front Solutions

Module (Primary)

57X0300 Contact Authentication Device 57X0301 Contactless Authentication

Device

82S12O3 IPDS License 82S12O4 Bar Code License

P/N Connectivity
1021231 Parallel (10') Cable
1021294 USB (2 Meter) Cable

14F0100 RS-232C Serial Interface Card 27X0142 Lexmark MarkNet™ N8230 Fiber Ethernet Print Server

37X6146 Fax Card Option 57X7040 English Keyboard Kit SPD0001 Surge Protective Device,

110-120V

P/N Furniture 20L8806 Cabinet 20L8807 Keyboard Shelf

| <b>Product Specifications</b>                    | Lexmark CX962tse   |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Printing   |  |  |  |  |  |  |
| Display  | Lexmark e-Task 10.1-inch (25.6 cm) class colour touch screen   |  |  |  |  |  |
| Print Speed                                      | Up to: Black: 45 ppm 1 (Letter) / Colour: 45 ppm 1 (Letter)  |  |  |  |  |  |
| Time to First Page                               | as fast as: Black: 71 seconds / Colour: 8.2 seconds  |  |  |  |  |  |
| Print Resolution                                 | Black: 1200 x 1200 dpi, 4800 Color Quality / Colour: 4800 Color Quality, 1200 x 1200 dpi   |  |  |  |  |  |
| Memory   | Standard: 4 GB / Maximum: 4 GB   |  |  |  |  |  |
| Hard Disk  | Intelligent Storage Drive included; Magnetic Hard Disk (optional)  |  |  |  |  |  |
| Recommended Monthly Page Volume                  | 7000 - 50000 pages <sup>2</sup>  |  |  |  |  |  |
| Maximum Monthly Duty Cycle                       | Up to: 200 000 pages per month <sup>3</sup>  |  |  |  |  |  |
| Copying  |  |  |  |  |  |  |
| Copy Speed                                       | Up to: Black: 45 cpm <sup>1</sup> (Letter) / Colour: 45 cpm <sup>1</sup> (Letter)  |  |  |  |  |  |
| Time to First Copy                               | as fast as: Black: 8.5 seconds / Colour: 9.5 seconds   |  |  |  |  |  |
| Scanning   |  |  |  |  |  |  |
| Scanner Type / ADF Scan                          | Flatbed scanner with automatic document feeder / DADF (single pass Duplex)   |  |  |  |  |  |
| A4/Ltr Duplex Scan Speed                         | Up to: Black: 240/240 sides per minute / Colour: 240/240 sides per minute  |  |  |  |  |  |
| A4/Ltr Simplex Scan Speed                        | Up to: Black: 120/120 sides per minute / Colour: 120/120 sides per minute  |  |  |  |  |  |
| ADF Paper Input Capacity                         | Up to: 300 pages 20 lb or 75 gsm bond  |  |  |  |  |  |
| Supplies 4                                       |  |  |  |  |  |  |
| Laser Cartridge Yields                           | up to: 46,900 <sup>5</sup> -page Colour (CMY) Cartridges / up to: 47,700 <sup>5</sup> -page Black Cartridge  |  |  |  |  |  |
| Imaging Unit Estimated Yield                     | Up to: 225,000 (black) and 250,000 (colour) pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/   |  |  |  |  |  |
|  | CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers   |  |  |  |  |  |
| Cartridge(s) Shipping with Product               | 15,000 <sup>5</sup> -page Black Toner Cartridge <sup>5</sup> , 12,000 <sup>5</sup> -page Colour (CMY) Toner Cartridges <sup>5</sup>  |  |  |  |  |  |
| Paper Handling                                   | isjood page stack is in: cardiage , 12,000 page colour (cirr) lone, cardiages  |  |  |  |  |  |
| Included Paper Handling                          | 500-Sheet Output Bin, 550-Sheet Tray, 550-Sheet Tray, 2 x 550-Sheet Tray, 150-Sheet Multipurpose Feeder  |  |  |  |  |  |
| Optional Paper Handling                          | 2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole  |  |  |  |  |  |
| optional raper manaling                          | Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tandem Tray, Cabinet  |  |  |  |  |  |
| Paper Input Capacity                             | Up to: Standard: 2350 pages 20 lb or 75 gsm bond / Maximum: 3850 pages 20 lb or 75 gsm bond  |  |  |  |  |  |
| Paper Output Capacity                            | Up to: Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 2650 pages 20 lb or 75 gsm bond   |  |  |  |  |  |
| Media Types Supported                            | Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide   |  |  |  |  |  |
| Media Sizes Supported                            | A6, Oficio, 12 x 18", 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope |  |  |  |  |  |
| General Information                              |  |  |  |  |  |  |
| Standard Ports                                   | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)                                    |  |  |  |  |  |
| Optional Network Ports / Optional Local<br>Ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial  |  |  |  |  |  |
| Noise Level                                      | Operating: 50 dBA (Print) / 52 dBA (Copy) / 50 dBA (Scan)  |  |  |  |  |  |
| Specified Operating Environment                  | Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)  |  |  |  |  |  |
| Limited Warranty                                 | See Statement of Limited Warranty: 1-Year Onsite Repair, Next Business Day   |  |  |  |  |  |
| Size / Weight                                    | H x W x D: 1220 x 592 x 660 mm / 120.7 kg  |  |  |  |  |  |
| ENERGY STAR Typical Electricity<br>Consumption   | TEC: 0.69 kilowatt-hours per week  |  |  |  |  |  |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2024 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



<sup>&</sup>lt;sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.